


| | | | |
|-------|----------------------------------|--------|-------------------------------|
| d mm | Wire diameter | L1 mm | Prestressed spring length |
| D mm | Mean coil diameter | L2 mm | Loaded spring length |
| De mm | Outer coil diameter | Ln mm | Maximum spring length |
| Dh mm | Minimum diameter of bush | m mm | Loop opening width |
| F0 N | Initial tension | n pc. | Number of aktive coils |
| F1 N | Prestressed spring force | nt pc. | Total number of coils |
| F2 N | Loaded spring force | s1 mm | Prestressed spring deflection |
| Fn N | Maximum spring force | s2 mm | Loaded spring deflection |
| Lh mm | Loop height | sn mm | Maximum spring deflection |
| Lk mm | Lenght of unstressed spring body | sh mm | Excursion |
| L0 mm | Unstressed spring length | R N/mm | Spring rate |

Weight g Weight of one spring

*Loops are stocked without openings (m = 0,00). However it is possible to have an opening cut into the loop at an extra cost, without causing any delay.



n nt R 0,210 Weight 63,340

Spring test acc. to DIN ISO 2859/1 test level II

| 1 Coiling direction <input type="checkbox"/> left <input checked="" type="checkbox"/> right | | 4 Stress cyc. end. N <input type="text"/> | | 10 Tolerances to DIN 2097 | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|-------------------------------------|--|-------------------------------------|---|-------------------------------------|--|---------|-------------------------------------|--|----------|-----------------------------|---|--------------------------|--------------------------|---|--------------------------|--------------------------|---|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|---|--------------------------|--------------------------|--------------------------|--------------------------|-------------------------------------|
| 2 Loop shape and loop position Loop shape: <input type="text" value="1/1 German loop"/> Loops offset to one another by <input type="text" value="270,0"/> \pm <input type="text" value="57,0"/> degrees (in the dir. of the right helix) | | 5 Stress cycle frequ. n <input type="text"/> / <input type="text"/> | | <table border="1"> <thead> <tr> <th>Grade</th> <th>De,Di,D</th> <th>L0</th> <th>F0-Fn</th> <th>Loops</th> <th>Wire diameter d to DIN 2076</th> </tr> </thead> <tbody> <tr> <td>1</td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> </tr> <tr> <td>2</td> <td><input checked="" type="checkbox"/></td> <td><input checked="" type="checkbox"/></td> <td><input checked="" type="checkbox"/></td> <td><input checked="" type="checkbox"/></td> <td><input checked="" type="checkbox"/></td> </tr> <tr> <td>3</td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input checked="" type="checkbox"/></td> </tr> </tbody> </table> | | Grade | De,Di,D | L0 | F0-Fn | Loops | Wire diameter d to DIN 2076 | 1 | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | 2 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | 3 | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> |
| Grade | De,Di,D | L0 | F0-Fn | Loops | Wire diameter d to DIN 2076 | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 Excursion sh <input type="text"/> mm | | 6 Application temp. <input type="text"/> °C | | 11 Production compensation through | | | | | | | | | | | | | | | | | | | | | | | | | |
| 7 Material <input type="text" value="EN 10270-1"/> | | 8 Wire or rod surface <input checked="" type="checkbox"/> drawn <input type="checkbox"/> rolled <input type="checkbox"/> metal-cut | | <table border="1"> <tr> <td>A spring resistance, associated length of tensed spring and L0</td> <td>F0, D</td> <td><input checked="" type="checkbox"/></td> </tr> <tr> <td>A spring resistance, associated length of tensed spring and F0</td> <td>L0, n, d</td> <td><input type="checkbox"/></td> </tr> <tr> <td></td> <td>L0, D</td> <td><input type="checkbox"/></td> </tr> <tr> <td>Two spring resistances and associated length of tensed spring</td> <td>L0, n, d</td> <td><input type="checkbox"/></td> </tr> <tr> <td></td> <td>F0,D</td> <td><input type="checkbox"/></td> </tr> </table> | | A spring resistance, associated length of tensed spring and L0 | F0, D | <input checked="" type="checkbox"/> | A spring resistance, associated length of tensed spring and F0 | L0, n, d | <input type="checkbox"/> | | L0, D | <input type="checkbox"/> | Two spring resistances and associated length of tensed spring | L0, n, d | <input type="checkbox"/> | | F0,D | <input type="checkbox"/> | | | | | | | | | |
| A spring resistance, associated length of tensed spring and L0 | F0, D | <input checked="" type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| A spring resistance, associated length of tensed spring and F0 | L0, n, d | <input type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | L0, D | <input type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Two spring resistances and associated length of tensed spring | L0, n, d | <input type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | F0,D | <input type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 9 Surface treatment <input type="text"/> | | 9 Surface treatment <input type="text"/> | | Prices | | | | | | | | | | | | | | | | | | | | | | | | | |

Remarks
 Származási ország: DE | Vámtarifaszám: 73202085

| Mennyiségi lépcsők | Egységár (EUR) |
|--------------------|----------------|
| 1 | 6,7100 € |
| 2 | 4,2300 € |
| 3 | 3,0800 € |
| 7 | 2,6300 € |
| 17 | 1,3800 € |
| 37 | 1,0500 € |
| 75 | 0,8600 € |
| 125 | 0,7979 € |
| 175 | 0,7848 € |
| 250 | 0,7607 € |
| 350 | 0,7408 € |
| 450 | 0,6532 € |