


α	degree	Unstressed leg position
$\alpha 1$	degree	Prestressed rotational angle
$\alpha 2$	degree	Loaded rotational angle
αh	degree	Excursion
αn	degree	Maximum rotational angle
d	mm	Wire diameter
Ddmin	mm	Min. possible mandrel diameter
Ddmax	mm	Max. possible mandrel diameter
De	mm	Outer coil diameter
Di	mm	Inner coil diameter
F1	N	Prestressed spring force
F2	N	Loaded spring force
Lk0	mm	Length of spring body when relaxed
LS	mm	Length of leg
M1	Nmm	Prestressed torque
M2	Nmm	Loaded torque
Mn	Nmm	Maximum torque
n	pc.	Active coils
RH	mm	Distance power flow point from centre
St	mm	Distance between coils (pitch)
Weight	g	Weight of one spring in grammes



Spring test acc. to DIN ISO 2859/1 test level II

1 Coiling direction <input checked="checked" type="checkbox"/> left <input type="checkbox"/> right		5 Excursion αh <input type="text"/> degr.		12 Tolerances to DIN 2194 <table border="1"> <tr> <th>Grade</th> <th>Di</th> <th>Lk0</th> <th>LSH,LSR</th> <th>$\alpha, \alpha 1, \alpha 2$</th> <th>M1, M2</th> <th>Wire diameter d to DIN 2076</th> </tr> <tr> <td>1</td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td></td> </tr> <tr> <td>2</td> <td><input checked="checked" type="checkbox"/></td> <td><input checked="checked" type="checkbox"/></td> <td><input checked="checked" type="checkbox"/></td> <td><input checked="checked" type="checkbox"/></td> <td><input checked="checked" type="checkbox"/></td> <td></td> </tr> <tr> <td>3</td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input checked="checked" type="checkbox"/></td> </tr> </table>			Grade	Di	Lk0	LSH,LSR	$\alpha, \alpha 1, \alpha 2$	M1, M2	Wire diameter d to DIN 2076	1	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		2	<input checked="checked" type="checkbox"/>	<input checked="checked" type="checkbox"/>	<input checked="checked" type="checkbox"/>	<input checked="checked" type="checkbox"/>	<input checked="checked" type="checkbox"/>		3	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="checked" type="checkbox"/>
Grade	Di	Lk0	LSH,LSR	$\alpha, \alpha 1, \alpha 2$	M1, M2	Wire diameter d to DIN 2076																												
1	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>																													
2	<input checked="checked" type="checkbox"/>	<input checked="checked" type="checkbox"/>	<input checked="checked" type="checkbox"/>	<input checked="checked" type="checkbox"/>	<input checked="checked" type="checkbox"/>																													
3	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="checked" type="checkbox"/>																												
2 Form of legs tangential, straight, no bends * *We can also supply torsion springs with any form of leg for an extra charge.		6 Stress cyc. end. N <input type="text"/>		13 Production compensation through A spring torque and the associated swing angle α <input checked="checked" type="checkbox"/> A spring torque and the associated swing angle and $\alpha 0$ <input type="checkbox"/> Two spring resistances and the associated swing angle <input type="checkbox"/>																														
3 Fixing Recumbent leg <input type="checkbox"/> Lever leg <input type="checkbox"/>		7 Stress cycle frequ. n <input type="text"/> /		through <input type="checkbox"/> through <input type="checkbox"/> through <input type="checkbox"/>																														
4 Load <input type="checkbox"/> in winding direction <input type="checkbox"/> against winding direction		8 Application temp. <input type="text"/> °C		10 Wire or rod surface <input checked="checked" type="checkbox"/> drawn <input type="checkbox"/> rolled <input type="checkbox"/> metal-cut																														
9 Material EN 10270-3-1.4310		11 Surface treatment <input type="text"/>		Prices <table border="1"> <tr> <th>Mennyiségi lépcsők</th> <th>Egységár (EUR)</th> </tr> <tr> <td>1</td> <td>5,5300 €</td> </tr> <tr> <td>2</td> <td>3,9000 €</td> </tr> <tr> <td>3</td> <td>3,7100 €</td> </tr> <tr> <td>7</td> <td>2,9000 €</td> </tr> <tr> <td>17</td> <td>1,4300 €</td> </tr> <tr> <td>37</td> <td>1,1000 €</td> </tr> <tr> <td>75</td> <td>0,9400 €</td> </tr> <tr> <td>125</td> <td>0,6511 €</td> </tr> <tr> <td>175</td> <td>0,6135 €</td> </tr> <tr> <td>250</td> <td>0,5760 €</td> </tr> <tr> <td>350</td> <td>0,5306 €</td> </tr> <tr> <td>450</td> <td>0,4927 €</td> </tr> </table>			Mennyiségi lépcsők	Egységár (EUR)	1	5,5300 €	2	3,9000 €	3	3,7100 €	7	2,9000 €	17	1,4300 €	37	1,1000 €	75	0,9400 €	125	0,6511 €	175	0,6135 €	250	0,5760 €	350	0,5306 €	450	0,4927 €		
Mennyiségi lépcsők	Egységár (EUR)																																	
1	5,5300 €																																	
2	3,9000 €																																	
3	3,7100 €																																	
7	2,9000 €																																	
17	1,4300 €																																	
37	1,1000 €																																	
75	0,9400 €																																	
125	0,6511 €																																	
175	0,6135 €																																	
250	0,5760 €																																	
350	0,5306 €																																	
450	0,4927 €																																	

Remarks

Származási ország: DE | Vámtarifaszám: 73202089